

BLATEMDELFIN ANTISALPICADO (ANTI-SPLASH)

DESCRIPTION



Water-based matt paint with an excellent covering power for interiors and exteriors except for facades, formulated with the most advanced technology in acrylic copolymers and styrene copolymers in emulsion, with pigments and charges of maximum quality.
Fireproof.

PROPERTIES

Excellent covering power and adhesion, good application properties, yield as well as wet rub and anti-splash resistance.

APPLICATION

For the painting of interiors and exteriors, except facades, on plaster, cement, bricks, fibre-cement, etc. When we would like to offer an excellent paint indoor with a very good balance of technical performances.

TECHNICAL CHARACTERISTICS

Appearance: smooth and matt.

Whiteness : excellent.

Wet rub resistance: Class 3, UNE-EN 1300.

Adhesion : excellent.

Fineness : $6,5 \pm 1$ H.G. (Hegman degree) (UNE-EN-ISO 1524).

Recoat time : 4 -6 hours.

Viscosity : 110 ± 15 uk (krebs units) at $25^{\circ} \pm 10$ °C.(UNE 48-076).

Density: $1,63 \pm 0,10$ gr/cc (UNE-EN-ISO 2811-1).

Covering power: Extraordinary.

Yield : 8 - 13 m²/ lt and coat.

Drying : 30-60 minutes.

Utensils: Cleaning with water.

Storage stability: Over a year in its sealed original packaging.

Not inflammable

V.O.C : 2004 / 42/ II (A/a) (75/30) Max. VOC's= 15 G/L.

APPROVALS AND TRIALS

Approval : reaction to fire ; UNE-EN standard 13501-1 :07 + A1 :2010. European classes : A₂, S₁, do.

SURFACE PREPARATION

New surfaces: remove loose particles, cover cracks, etc.

Painted surfaces:

-with tempera or lime: remove it previously.

-with paint: remove parts in bad conditions.

INSTRUCTIONS OF USE

Apply a first coat diluted with 15-25% of potable water and a second coat of 5-10% approximately. If applied by brush. If it is applied by roller, dilute with 5-10% and 10-25% in case of application by spray gun.

RECOMMENDATIONS

Do not paint in rainy weather or at temperatures below 5°C.
Stir the content of the container.
Do not wash before 20 days of its application.

PACKAGING

Available in 750ml, 4L, 12L and 15L.

STORAGE

Storage time : over a year in its sealed original packaging, protected from the elements (sheltered and at a temperature between 5 and 35°C).

SAFETY INFORMATION

It is indispensable to follow instructions on the packaging label.
For more information, please consult the safety data sheet of the product.

DATE...: 08/05/14

The data provided in these technical specifications have been made by the technical services of this company and they should be followed for proper product application.

As the application will be made by the client out of the possibility of control of the company, in case of not follow the instructions will be the sole responsibility of the customer.

It is also your responsibility not to take the appropriate measures in order to comply with legislation.

The information contained in this technical data sheet from this product are the knowledge from tests performed by the technical services of this company. But considering that the paintings in certain circumstances are beyond our control, especially in its application, we can only guarantee the quality of the product itself. The company reserves the right to modify the contents of this technical data sheet without notice.
