

BLATEM ACRYLIC ANTIOXIDANTE

Date: 14 / 06 / 2019



DESCRIPTION

Glossy water-based enamel, formulated with the most advanced technology to achieve good anti-rust performance. Direct application on iron.

PROPERTIES

- Antioxidant.
- Direct application on the base (iron).
- Excellent coverage and brushability
- Quick drying.
- Odourless.
- Excellent adhesion on most types of surfaces.

APPLICATIONS

For the protection of all surfaces, both indoor and outdoor, such as doors, windows, fences, handrails, garden furniture, etc, made of iron, wood and other building materials.

TECHNICAL CHARACTERISTICS

| | |
|------------------------|--|
| Finish | Gloss |
| Leveling | Excellent |
| Adhesion | Excellent. |
| Brushability | Excellent |
| Drying | 2 - 4 hours |
| Recoat time: | 18 - 24 hours |
| Viscosity (UNE 48-076) | 100 ± 10 U.K.(krebs Units) a 25 ± 8°C. |

| | |
|--|--------------------------------------|
| Density (UNE-EN-ISO 2811-1 and 2) | 1,200 ± 0,10 gr/cc |
| Fineness (UNE-EN-ISO 1524) | 7,5±1 HG (Hegman degrees) |
| Coverage | 9-11 m ² /l per coat. |
| Film thickness: | Minimum 120 microns dry. |
| Hardness | Good |
| Conservation | a year in original sealed container. |
| Utensils | Cleaning with water |
| Limit value by the EU for the products (Cat. A/i): 140 g/L (2010). Maximum VOC content: 120 g/L. | |

SURFACE PREPARATION

- Surfaces must be clean, dry and free of loose rust.
- **Unpainted metal surfaces:**
 - Iron, steel, oxide: Remove rust and mill scale by mechanical or manual brushing and degrease. If greater anti-rust protection is desired, apply our Magneton rust converter beforehand and finish with Blatemacrylic Antioxidante.
 - Galvanized and light metals: Degrease and check adhesion.
- **Painted surfaces:**

If the paint is well bonded, wash and sand, removing dust before applying Blatem Acrylic Antioxidante. If there is no security, or the paint is not properly bonded, remove it and proceed as unpainted surface.

 - Always use the recommended final thickness to obtain the right anti-rust protection, 120 dry microns of Blatemacrylic Antioxidante.

Pinturas Blatem S.L.

Ctra. Masía del Juez, 36 • 46909 TORRENT (Valencia, España) • Telf.: (34) 96 155 00 73 • Fax: (34) 96 157 37 20 • E-mail: blatem@blatem.com

www.blatem.com

Los datos suministrados en esta ficha técnica han sido realizados por los servicios técnicos de esta empresa y los mismos deben seguirse para una correcta aplicación del producto. La aplicación del producto está fuera del alcance de nuestra posibilidad de control, en el supuesto de no seguirse las instrucciones indicadas será exclusiva responsabilidad del cliente. Será igualmente responsabilidad del cliente no tomar las medidas adecuadas con el objeto de cumplir las legislaciones vigentes. La información que consta en la presente ficha técnica responde al conocimiento del producto en ensayos realizados por los servicios técnicos de esta empresa. Pero teniendo en cuenta que las pinturas en determinadas circunstancias escapan a nuestro control, sobre todo en su aplicación, no podemos garantizar más que la calidad propia de la pintura, reservándose esta empresa el derecho a modificar el contenido de los datos de esta ficha técnica sin previo aviso.

BLATEM ACRYLIC ANTIOXIDANTE

Date: 14 / 06 / 2019

INSTRUCTIONS FOR USE

Homogenize the product prior to application.
Application temperature between 5 and 35°C.
Do not apply the product when humidity is equal to or above 80%.
Applied as it is using a brush or roller, without previous dilution.
For application with a paint gun, dilute the product with 10-20% water.
Wash painting tools with water immediately after use
Apply at least two coats.

RECOMMENDATIONS

Stir the content of the container until the product is homogenized. Do not paint in rainy weather or at temperatures below 5°C.
Wash the utensils with water immediately after use.

PACKAGING

- Available in : 750 ml
- Colours: Blanco (White), negro (black), gris perla (Pearl Grey), verde carruajes (Green Carriage).

STORAGE

Storage time: over a year in its sealed original packaging, protected from weathering (sheltered and at a temperature between 5 and 35°C).

SAFETY INFORMATION

Harmful to aquatic life with long lasting effects. Contains a preservative to control microbial deterioration: CMIT/MIT (CAS: 55965-84-9), BIT (CAS: 2634-33-5). May produce an allergic reaction. Safety data sheet available on request. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Dispose of the contents/containers in accordance with the current legislation on waste treatment.

Pinturas Blatem S.L.

Ctra. Masía del Juez, 36 • 46909 TORRENT (Valencia, España) • Telf.: (34) 96 155 00 73 • Fax: (34) 96 157 37 20 • E-mail: blatem@blatem.com

www.blatem.com

The data provided in this data sheet have been made by the technical services of this company and they must be followed for a correct application of the product. Any application carried out by the client without any possibility of control and prior consent from our company, in case of not following the instructions indicated, will be the sole responsibility of the client. It will be also the responsibility of the client not to take the appropriate measures in order to comply with the legislation in force. The information in this technical sheet is based on the knowledge of the product following to tests carried out by the technical services of this company. But taking into account that paints are beyond our control in certain circumstances, especially regarding their application, we cannot guarantee more than the quality of the paint itself. This company reserves the right to modify the content of the data of this technical sheet without previous notice.

