



Evolución Constante

Ctra. Masía del Juez, 36 46909 TORRENT (Valencia) SPAIN TEL: (34) 961 550 073 FAX: (34) 961 573 720 E-mail: blatem@blatem.com

visit us at: www.blatem.com

Technical data sheet

BLATEPLAS PREMIUM CON CONSERVANTE ANTIMOHO



DESCRIPTION

Acrylic matte paint with very high covering power and high quality for interior and exterior, formulated with the most advanced technology with high quality styrene acrylic copolymers, pigments and charges.

PROPERTIES

Extraordinary covering power, adhesion and whiteness; very good application properties, yield, wet scrub resistance, anti-splash and anti-mould.

APPLICATIONS

For interior and exterior decoration, on plaster, cement, brick, fibre cement, etc...when a high covering power is required as well as very good technical properties in general.

TECHNICAL CHARACTERISTICS

Appearance: smooth and matte.
 Covering power: extraordinary.
 Whiteness: excellent.
 Adhesion: excellent.
 Wet scrub resistance: Class 2 (UNE-EN 13.300).
 Fineness: $6,5 \pm 1$ HG (Hegman Grades) (UNE-EN ISO 1524).
 Viscosity: 130 ± 15 UK (Krebs Units) at $25 \pm 10^\circ\text{C}$ (UNE 48-076).
 Density: $1,61 \pm 0,10$ gr/cc (UNE-EN-ISO 2811-1).
 Yield: 8-13 m²/L and coat.
 Drying: 30-60 minutes.
 Overcoating: 4-6 hours.
 Utensils: Water cleaning.
 Conservation: over a year in its original and sealed packaging.
 Non-flammable.
 V.O.C.: 2004/42/II (A/a) (75/30) Max. VOC: 15 G/L.

SURFACE PREPARATION

New surfaces: remove loose particles, cover cracks, etc.
 Painted surfaces: with tempera or lime, remove previously.
 With paint, remove parts in poor condition.

INSTRUCTIONS FOR USE

Apply one coat diluted with 20%-30% of drinking water and a second coat with 10% approximately.

Apply with a brush, roller (dilution 5-10%) and spray-gun (dilution 10-25%).

If the surface has adhesion problems, apply previously our primer "Fijador Acrílico"(Acrylic Fixative) or "Fijador al Disolvente" (Solvent-based Fixative).

RECOMMENDATIONS

Do not paint in rainy weather or at temperatures below 5°C.

Stir the content of the container before use.

Do not paint the painted surface before 20 days.

PRESENTATION

Available in 750 ml, 4L and 15L.

STORAGE

Storage time: Over a year in its sealed and original packaging, protected from the elements (sheltered and at a temperature between 5°C and 35°C).

SAFETY INFORMATION

It is necessary to follow the instructions shown on the package label.

For more information, please refer to the safety data sheet.

FECHA..: 24/02/17

The data provided in these technical specifications have been made by the technical services of this company and they should be followed for proper product application.

As the application will be made by the client out of the possibility of control of the company, in case of not follow the instructions will be the sole responsibility of the costumer.

It is also your responsibility not to take the appropriate measures in order to comply with legislation.

The information contained in this technical datasheet from this product are the knowledge from tests performed by the technical services of this company. But considering that the paintings in certain circumstances are beyond our control, especially in its application, we can only guarantee the quality of the product itself. The company reserves the right to modify the contents of this technical datasheet without notice.
