



Evolución Constante

Ctra. Masía del Juez, 36 46909 TORRENT (Valencia) SPAIN TEL: (34) 961 550 073 FAX: (34) 961 573 720 E-mail: blatem@blatem.com

visit us at: www.blatem.com

Technical data sheet

BLATEM NORDIC WHITE CON CONSERVANTE ANTIMOHO

(with anti-mold preservatives)



DESCRIPTION

High quality matt paint for interiors and exteriors (except facades), formulated with the latest technology in acrylic-styrene emulsion copolymers, with pigments, fillers and additives of the highest quality.

PROPERTIES

Properties include excellent coverage, adhesion, whiteness, very good application, performance, wet scrub resistance and AntiSplash technology.

With a neutral white tone.

APPLICATIONS

Ideal for interior and exterior decoration, over various types of plasters, cement, brick, fibrecement, etc ... In general, when a high level of coverage and very good technical properties are required.

TECHNICAL CHARACTERISTICS

Colour: white (neutral).

Appearance: smooth and matt.

Covering power: excellent.

Whiteness: excellent.

Adhesion: excellent.

Wet scrub resistance: Class 3 (UNE-EN 13.300).

Fineness: $6,5 \pm 1$ hg (hegman gauge) (UNE-EN-ISO 1524).

Viscosity: 110 ± 15 ku (krebs units) at 25 ± 10 °c.(UNE 48-076).

Density: $1,64 \pm 0,10$ gr/cc.(UNE-EN-ISO 2811-1).

Coverage: 8 - 11 m²/ lt and coat Drying: 30-60 minutes.

Recoat time: 4-6 hours.

Utensils: cleaning with water.

Storage: over a year in its sealed original packaging.

Non-flammable.

V.O.C: 2004 / 42 / II (A/a) (75/30) max. VOC= 15 gr/lt.

SURFACE PREPARATION

New surfaces (unpainted), remove loose parts, cover cracks, etc.

Surfaces painted with lime or tempera, remove them previously.

Painted surfaces, remove loose parts.

INSTRUCTIONS FOR USE

Apply the paint barely undiluted, normally one coat is enough. If necessary (due to the colour of the substrate), apply a second coat.

Apply with brush, roller or spray gun. Dilution with water is approximately: 10% for brush or roller and 20% for spray gun. If the surface presents special adhesion problems, prime previously with our acrylic fixative or solvent-based fixative.

RECOMMENDATIONS

Do not paint in rainy weather or at temperatures below 5°C.

Stir the content of the container.

Do not wash the painted surface before 20 days after application.

PACKAGING

Available in 4L and 15L.

STORAGE

Storage time: over a year in its sealed original packaging, protected from weathering (sheltered and at a temperature between 5 and 35°C).

SAFETY INFORMATION

Contains CMIT/MIT n°CAS 55965-84-9, BIT n°CAS 2634-33-5 and DCOIT n°CAS 64359-81-5.

May cause an allergic reaction.

Safety data sheet available on request.

Keep out of reach of children.

Read the package label before use.

FECHA.: 12/09/18

The data provided in these technical specifications have been made by the technical services of this company and they should be followed for proper product application.

As the application will be made by the client out of the possibility of control of the company, in case of not follow the instructions will be the sole responsibility of the costumer.

It is also your responsibility not to take the appropriate measures in order to comply with legislation.

The information contained in this technical datasheet from this product are the knowledge from tests performed by the technical services of this company. But considering that the paintings in certain circumstances are beyond our control, especially in its application, we can only guarantee the quality of the product itself. The company reserves the right to modify the contents of this technical datasheet without notice.
