



Evolución Constante

Ctra. Masía del Juez, 36 46909 TORRENT (Valencia) SPAIN TEL: (34) 961 550 073 FAX: (34) 961 573 720 E-mail: blatem@blatem.com



visit us at: www.blatem.com

Technical data sheet

FENG-SHUI (COLOURS)



DESCRIPTION

Vinyl matt covering plastic paint available in 25 colours, formulated to prevent roller marks and joints indoor.

PROPERTIES

Excellent range of colours, very good matt level and coverage as well as high performance and application properties with good washability and adhesion.

APPLICATIONS

Decoration of any normal building supports to provide a finish without roller marks or splices. Especially suitable for smooth indoor walls.

TECHNICAL CHARACTERISTICS

Appearance: smooth and matt.
Colour: range of 25 colours.
Wet scrub resistance: class 2 (UNE-EN 13.300).
Adhesion: good.
Fineness: $6,2 \pm 1$ H.G. (Hegman rating) (UNE-EN-ISO 1524).
Viscosity: 110 ± 15 U.K. (Krebs Units) at $25 \pm 10^\circ\text{C}$ (UNE 48-076).
Density: 1,44 - 1,59 gr/cc depending on colour (UNE-EN-ISO 2811-1).
Covering power: high.
Performance: 9-13 m²/L and coat.
Drying: 30-60 minutes.
Overcoat: 4-6 hours.
Utensils: water cleaning.
Conservation: over one year in its original and sealed packaging.
Non-flammable.
V.O.C.: 2004/42/IIA (A/a)(75/30) Max.COVS: 15 G/L.

PREPARATION OF SURFACES

New surfaces: remove dirt, loose particles, cover cracks, etc.
Painted surfaces: with tempera or lime: remove previously. With paint, remove loose parts in bad conditions and low quality.

INSTRUCTIONS FOR USE

Apply our Acrylic Sealer "Fijador Acrílico" (surfaces with possible adhesion problems) or with diluted paint with 20-30% of drinking water. Apply the paint normally without diluting: one coat should be enough, apply a second coat if necessary.
Application with a brush, roller or spray gun.

RECOMMENDATIONS

Do not paint at temperatures below 5°C.
Stir the content of the container before use.
Do not wash the painted surface before 20 days.

PRESENTATION

Available in 2,5L.
Colours: range of 25 colours according to sample.

STORAGE

Storage time: Over one year in its sealed and original packaging, protected from the elements (sheltered and at a temperature between 5°C and

35°C).

SAFETY INFORMATION

It is necessary to follow the instructions shown on the package label.
For more information, please consult the safety data sheet.

FECHA...: 12/09/16

The data provided in these technical specifications have been made by the technical services of this company and they should be followed for proper product application.

As the application will be made by the client out of the possibility of control of the company, in case of not follow the instructions will be the sole responsibility of the customer.

It is also your responsibility not to take the appropriate measures in order to comply with legislation.

The information contained in this technical datasheet from this product are the knowledge from tests performed by the technical services of this company. But considering that the paintings in certain circumstances are beyond our control, especially in its application, we can only guarantee the quality of the product itself. The company reserves the right to modify the contents of this technical datasheet without notice.
