



Evolución Constante

Ctra. Masía del Juez, 36 46909 TORRENT (Valencia) SPAIN TEL: (34) 961 550 073 FAX: (34) 961 573 720 E-mail: blatem@blatem.com

visit us at: www.blatem.com

Technical data sheet

BLATEM PRIMER (FIJADOR SELLADOR ACRILICO BLANCO)



DESCRIPTION

Water-based white sealer/fixative, high covering power, specially formulated to fix and prepare exterior and interior walls.

PROPERTIES

High covering power, great penetration and easy application for an uniform finish on normal building materials.

APPLICATIONS

To use as a primer before applying our stuccos (Estuco Palace, etc). and for interior and exterior use before applying any water-based paint (plastic paints, except satin or very thin, coatings, waterproofing coatings, etc.) to improve finish covering.

TECHNICAL CHARACTERISTICS

Finish: White. Slightly granulated.
 Covering power: Excellent.
 Sealing: Excellent.
 Drying: 30-60 minutes.
 Overcoat: 4-6 hours.
 Viscosity: 85 ± 20 UK (Krebs Units) at $25 \pm 10^\circ\text{C}$ (UNE 48.076).
 Density: $1,45 \pm 0,10$ gr/cc (UNE-EN-ISO 2811-1).
 Yield: 5-8 m²/L and coat (diluted).
 Utensils: Water cleaning.
 Conservation: over a year in its original and sealed packaging.
 Non-flammable.
 V.O.C.: 2004/42/II (A/h) Max. VOC: 20 G/L.

SURFACE PREPARATION

Surfaces must be clean and dry.

INSTRUCTIONS FOR USE

Dilute the product with 25%-50% of drinking water according to the required support penetration except when our acrylic mortars Torval Mortero Acrílico and Torval Rayado Mortero Acrílico are applied over the product, it should be diluted with 0-10% of drinking water.

Apply usually with a roller or a brush.

RECOMMENDATIONS

Do not paint in rainy weather, nor at temperatures below 5°C.
Stir the content of the container before use.

PRESENTATION

Available in 750 ml, 4L and 15L.

STORAGE

Storage time: Over a year in its sealed and original packaging, protected from the elements (sheltered and at a temperature between 5°C and 35°C).

SAFETY INFORMATION

It is necessary to follow the instructions shown on the package label.
For more information, please refer to the safety data sheet.

FECHA.: 24/02/17

The data provided in these technical specifications have been made by the technical services of this company and they should be followed for proper product application.

As the application will be made by the client out of the possibility of control of the company, in case of not follow the instructions will be the sole responsibility of the costumer.

It is also your responsibility not to take the appropriate measures in order to comply with legislation.

The information contained in this technical datasheet from this product are the knowledge from tests performed by the technical services of this company. But considering that the paintings in certain circumstances are beyond our control, especially in its application, we can only guarantee the quality of the product itself. The company reserves the right to modify the contents of this technical datasheet without notice.
