

BLATEMLUX BRILLANTE (GLOSS)



DESCRIPTION

Gloss synthetic enamel of extraordinary quality for interiors and exteriors, formulated with the most advanced technology to achieve maximum performances.

PROPERTIES

Excellent whiteness and excellent resistance to the yellowing of white color, covering power, brilliance, yield, brushability and levelling, as well as good drying and high resistance to blows, graze and cleaning products.

APPLICATION

For the painting of all kind of surfaces of wood, masonry and iron duly prepared indoor and outdoor. We recommend it for its excellent resistance in exterior specially for steel protection (as finish coat).

TECHNICAL CHARACTERISTICS

Finish: Gloss white and colors according to finish sampling.

Levelling: Excellent.

Adhesion: Excellent.

Brushability: Excellent.

Drying: 4 ± 2h at 25±8°C depending on the color.

Recoat time: 18-24 hours.

Viscosity: 170 ± 50" F-4 (Ford cup nº 4) at 25° ± 8°C depending on the color (ASTM D-1200).

Densidad: 1,20 ± 0,30 gr/cc. Depending on the color (UNE-EN-ISO 2811-1 and 2).

Fineness: 7,5 ± 1 HG (Hegman degree) (UNE-EN-ISO 1524).

Yield: 12-15 m²/Lt and coat.

Film thickness: 65-85 wet microns (approx. 30-40 dry microns).

Hardness: Good.

Stockage stability: More than a year in its sealed original package.

Utensils: Cleaning for solvent for enamels, Cleaning solvent or Universal solvent VOC: 2004/42/IIA (d) (400/300) Max. VOCS 299 g/l.

SURFACE PREPARATION

New surfaces: -Iron: deoxidize and degrease the surface, apply a first coat of Antioxidant Minium "Minio Antioxidante" or Antioxidant Blatprimer "Blatprimer Antioxidante".

After 24 hours, Apply Blatemlux.

-Galvanized iron, aluminium and zinc: clean and degrease the surface, apply multi-usage primer "Imprimación Multiuso", Water-based multiadherent Blatemprim "Blatemprim Multiadherente al agua", etc. and paint with Blatemlux.

-Wood: Apply our synthetic sealer "Selladora Sintética", sand and clean dust; and then apply Blatemplux.

Painted surfaces: -If they are in good conditions, gently sand and clean with Solvent for enamels before applying Blatemplux.

-If they are in bad conditions, remove the paint, apply first coat and paint with Blatemplux as for new surfaces.

INSTRUCTIONS OF USE

It can be applied with brush, roller or spray gun, ready to use. Do not apply on surfaces overheated by sunlight.

Apply always in thin layers according to technical details.

Apply the second coat respecting the recoat time.

RECOMMENDATIONS

Stir the content of the container until homgeneization of the product. After use, cover container to avoid air contact for later use.

PACKAGING

Available in 250ml, 750ml and 4L.

Colors: Snow white and 23 colors according to color chart.

STORAGE

Storage time : one year in its sealed original packaging, protected from the elements (sheltered and at a temperature between 5 and 35°C).

SAFETY INFORMATION

It is imperative to follow instructions on product label.

For more information, please consult the safety data sheet.

DATE...: 11/03/14

The data provided in these technical specifications have been made by the technical services of this company and they should be followed for proper product application.

As the application will be made by the client out of the possibility of control of the company, in case of not follow the instructions will be the sole responsibility of the costumer.

It is also your responsibility not to take the appropriate measures in order to comply with legislation.

The information contained in this technical data sheet from this product are the knowledge from tests performed by the technical services of this company. But considering that the paintings in certain circumstances are beyond our control, especially in its application, we can only guarantee the quality of the product itself. The company reserves the right to modify the contents of this technical data sheet without notice.
