

# BLATEMPRIM WATER-BASED MULTIADHESIVE PRIMER

Date: 05 / 10 / 2020



## DESCRIPTION

Water-based adhesive primer, made of special polymers, for preparing difficult-to-bond surfaces before painting.

## PROPERTIES

- Strong adherence to difficult substrates and those made of metal, plastic and ceramics.
- Can be repainted with solvent-based finishes (synthetics, polyurethanes and epoxies).
- Can be repainted with water-based finishes.
- Fast drying, does not become yellow with time.

## APPLICATIONS

Primer to be applied onto galvanised iron, aluminium, copper, PVC, ceramics, etc., both indoors and outdoors, ensuring the proper adherence of the paint or enamel finish.

## TECHNICAL CHARACTERISTICS

Colour	White
Finish	matte
Density	1,35 g/cc ± 0,1g/cc (UNE-EN-ISO 2811-1 y 2)
Viscosity	80 ± 15 UK a 25°C (UNE 48.076).
Fineness	6,5 HG ± 0,1 HG (UNE-EN-ISO 1524)
Dry (touch)	1-2 hours
Repainting	Min.: 8 hours; max.: No limits.
Performance	8-10 m <sup>2</sup> /Lt
Storage	Can be stored more than one year in its original cane
Tools	Clean with water

Not flammable

C.O.V. ; 2004/42/II (A/i) (140/140) MAX. COVS: 100 g/L.

## SURFACE PREPARATION

### Steel.

Maximum anti-corrosion protection, sandblasting up to SA 2 1/2.

Good anti-corrosive protection, hand tool cleaning st3.

Steel: Maximum anti-corrosion protection, sandblasting up to SA 2 1/2.

### Aluminium, galvanised material, copper, zinc, etc.

With a clean and lightly sanded surface.

## HOW TO USE

It can be applied with brush, roller or spray gun

For brush, roller dilution is 0-10% of drinking water. For spray gun dilution must be 10-20%

## RECOMMENDATIONS

- Remove properly the contents of the cane until full homogenization.
- Do not store open or started containers and keep containers away from the cold to prevent frost damage.

## PRESENTATION

- Available in 750ml and 4L Canes.

## STORAGE

Can be stored 24 months in its original cane, if perfectly closed, not outdoors and being temperature between 5 and 35°C.

### Pinturas Blatem S.L.

Ctra. Masía del Juez, 36 • 46909 TORRENT (Valencia, España) • Telf.: (34) 96 155 00 73 • Fax: (34) 96 157 37 20 • E-mail: blatem@blatem.com

[www.blatem.com](http://www.blatem.com)

The data provided in this data sheet have been made by the technical services of this company and they must be followed for a correct application of the product. Any application carried out by the client without any possibility of control and prior consent from our company, in case of not following the instructions indicated, will be the sole responsibility of the client. It will be also the responsibility of the client not to take the appropriate measures in order to comply with the legislation in force. The information in this technical sheet is based on the knowledge of the product following to tests carried out by the technical services of this company. But taking into account that paints are beyond our control in certain circumstances, especially regarding their application, we cannot guarantee more than the quality of the paint itself. This company reserves the right to modify the content of the data of this technical sheet without previous notice.

# BLATEMPRIM

## WATER-BASED MULTIADHESIVE PRIMER

Date: 05 / 10 / 2020

### ■ SAFETY INFORMATION

- Contains a preservative to control microbial deterioration: CMIT/MIT (CAS: 55965-84-9), BIT (CAS: 2634-33-5).
- May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Read label before use.
- Warning! Hazardous respirable droplets may be formed when sprayed.
- Dispose of the contents/containers in accordance with the current legislation on waste treatment.

#### Pinturas Blatem S.L.

Ctra. Masía del Juez, 36 • 46909 TORRENT (Valencia, España) • Telf.: (34) 96 155 00 73 • Fax: (34) 96 157 37 20 • E-mail: [blatem@blatem.com](mailto:blatem@blatem.com)

[www.blatem.com](http://www.blatem.com)

The data provided in this data sheet have been made by the technical services of this company and they must be followed for a correct application of the product. Any application carried out by the client without any possibility of control and prior consent from our company, in case of not following the instructions indicated, will be the sole responsibility of the client. It will be also the responsibility of the client not to take the appropriate measures in order to comply with the legislation in force. The information in this technical sheet is based on the knowledge of the product following to tests carried out by the technical services of this company. But taking into account that paints are beyond our control in certain circumstances, especially regarding their application, we cannot guarantee more than the quality of the paint itself. This company reserves the right to modify the content of the data of this technical sheet without previous notice.

